

Ergonomic, Elegant and Rugged

The DuraScan D750 is a professional grade, 2D/1D barcode scanner with Bluetooth® wireless technology. It delivers exceptional scanning abilities, providing advanced data editing capabilities, reading imperfect barcodes and providing omni-directional scanning. The LED-based aimer works clearly in both indoor and outdoor settings while the motion tolerance provides faster scans, as well as extended scanning range, like scanning with a laser. Ideal for scan-intensive applications where productivity is key, but lasers are prohibited.

The highly durable exterior was built for applications in warehouses, outdoor distribution, industrial manufacturing conditions, automotive, healthcare, logistics, and more. The scanner's IP54-rated outer casing withstands dust and water splashes, while its antimicrobial material helps protect from germs.









Certified by Apple® for iOS devices (iPad®, iPhone®, iPod Touch®) and compatible with Android and Windows®.







Features

- Bluetooth Wireless Technology Compatible with iOS, Android and Windows devices with typical Bluetooth range of 30 meters (98 feet), class 2.
- Certified by Apple® for iOS devices Guaranteed Compatibility With our SDK integrated in over 700+ applications, Socket Mobile scanners are one of the most natively integrated scanners available today. Socket Mobile Scanners are also 100% compatible with any application out-of-the-box in HID (keyboard emulation) mode.
- Compatible with all Android and Windows devices and applications
- Scanning Rapid 2D & 1D omni-directional barcode scanning with highly visible and safe LED aimer, suited for environments prohibiting lasers
- **Decoding Ability** Reads damaged, poorly printed, overlaid or colored barcodes. The scanner corrects many barcode imperfections.
- Motion Tolerance Allows for faster scanning (steady hands not required).
- LED Aimer Safe, yet pronounced, highly visibly red LED scanning line (easily aims in low light or indoor environment).
- User Indicators Intuitive LEDs, Bluetooth connection, battery level and scanning status
- User Feedback Audible tones and hand pulsation
- Exceptional Ergonomics Small, lightweight, and fits perfectly in the hand for comfortable use over extended periods.
- Data Editing Add or remove characters and control characters
- Long lasting Battery Power to last over 16 hours
- Rugged Design Protection rating of IP54 for dust and water splashing protection. Withstands multiple drops to concrete and repeated tumbles.
- Auto Scan Mode Provides continuous scanning capabilities without pressing scan button.
- Protective Material Made with antimicrobial additives to help protect against harmful bacteria.
- Application Integration Socket Mobile's Capture SDK enables easy integration in your applications to improve business productivity with fast, efficient and reliable data transfer over Bluetooth wireless technology.
- Wearable Includes lanyard/belt clip. Holster and Durable Retractable Clip available (sold separately)
- Designed and Assembled in the USA
- Developer Support Available
- 1-Year Warranty

SCANNING PERFORMANCE

Default Barcode 1D symbologies: Codabar, Code 39, Code 93/93i, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1-Symbologies: 128, UPC A, UPC E0

2D symbologies: Aztec, Data Matrix, Maxicode, Micro PDF417, QR Code

Postal Codes: Australian Post

Supported Barcode Symbologies:

1D symbologies: Codabar, Code 11, Code 39, Code 93/93i, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 DataBar Expanded Stacked, GS1 DataBar Limited, GS1-128, Interleaved 2 of 5, ISBN, ISBT 128,

Matrix 2 of 5, MSI, Standard 2 of 5, Telepen, UPC/EAN, UPC A, UPC E0


2D symbologies: Aztec, Codablock, Data Matrix, Maxicode, Micro PDF417, PDF417, QR Code Postal Codes: Australian Post, BPO, Canada Post, Dutch Post, Japan Post, Sweden Post, Postnet

Scan Angle: 39° (Horizontal) - 25.5° (Vertical)

Optical Resolution: 752 (H) x 480 (V) pixels, 256 gray levels

Print Contrast: Down to 30%

Reading Distance:



1D codes 4.5 to 90 cm (1.97 in to 35.43 in) 2D codes 4.5 to 40 cm (1.97 in to 15.75 in) Depends on barcode size, symbology, label media

SCANNER TYPE

Technology: 2D/1D Barcode Imager with highly visible LED aimer

Light Source: Highly Visible white LED.

617 nm Red LED Aimer:

BATTERY

Battery: 1400 mAh Lithium - Ion Battery

Charge Time: 6 Hours

Battery Life -

Standby time: over 30 hours Per Full Charge: Active Scan Time: 70,000 scans within 9 hours (based on 2 scans every 1 second)

14,000 scans within 16 hours (based on 1 scan every 4 seconds)

Note: Battery life varies depending on ambient temperature, ambient light and age of battery.

BLUETOOTH (WIRELESS CONNECTION)

Bluetooth Radio: Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption

Bluetooth Range: Up to 30 meters (98 ft.) depending on environment, range limit is usually due to the Host Device (phone,

tablet or notebook)

PHYSICAL CHARACTERISTICS



USER ENVIRONMENT

Ambient Light: From 0 to 100 000 lux, From pitch black to direct sun light

Operating -20° to 50° C (-4° to 122° F)

Temperature:

Storage Temperature: -40° to 70° C (-40° to 158° F)

Relative Humidity: 95% at 60° C (140° F) (non-condensing)

Sealing: IP54 (Ingress Protection rating for dust and water) EN60529

Drop Specifications: Multiple 5 ft. drops to concrete

Tumble Specification: 250 cycles at 1.64 ft. (0.5 m) (500 drops), IEC60068-2-31, IEC60068-2-32

OPERATING SYSTEM COMPATIBILITY

Android OS - Basic Mode (HID)* & Application Mode (SPP) Mac OS - Basic Mode (HID)* only

Apple iOS - Basic Mode (HID)* & Application Mode (MFi-SPP) Windows OS - 10, 8, and 7 - Basic Mode (HID)* & Application Mode

(SPP

Compatible with devices supporting Basic Mode (HID)* protocol

Supported keyboard languages - English, French, German and Spanish

*By default the scanner is in Basic Mode (HID).

Certified by Apple® for iOS devices (iPad®, iPhone®, iPod Touch®) and compatible with Android and Windows®.











CERTIFICATION & REGULATORY

Bluetooth SIG: Declaration ID: D030473 QD ID: 82009

Electrical Safety: Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2

Environmental: Environmental: RoHS EN 50581

EMI / RFI: FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC

FCC ID: LUBD750 IC ID: 2925A-D750 CMITT ID: 2016DJ7651 Telec ID: R 211-161214

LED Safety: IEC/EN 62471 (EXEMPT GROUP)















SRRC





WARRANTY

Scanner: Standard one year limited warranty

Accessories: 90 days

Extended Warranty: www.socketmobile.com/socketcare

(sold separately)



COMMON USES

Retail/Point of Sale	Warehouse management	Transportation
Office use	Shipping & Receiving	Gaming
Healthcare	Field Sales/Service	Hospitality
Mobile Tracking	Banking	

SINGLE PACKAGE INCLUDES

- (1) DuraScan D750, 2D/1D Barcode Imager
- (1) Charging Cable
- (1) Durable Lanyard
- (1) Get Started Insert



The D750 is available in 3 colors:


Utility Gray (SKU# CX3359-1681) Safety Green (SKU# CX3380-1773) Construction Orange (SKU# CX3382-1775)

OPTIONAL ACCESSORIES



Great for using AutoScan Mode

Charging Cradle





Provides quick access to scanner



Safe and accessible placement



Ideal as a desktop charger

Wrist Strap or Lanyard



+1 800 552 3300 (USA/Canada)

+33 970 462 241 France: Latin America: +1 510 933 3153

+1 510 933 3122 Asia Pacific: +49 9401 5299 052

+41 62 834 0780 EMEA & Russia:

+8190 9808 0518

+44 (0) 1252 761403 +44 7787 112109 UK/Ireland/South Africa:

+41 62 834 07 80